

GÖLZ FB200 • Hand held drill petrol

- Drill range Ø50-200mm
- Exhaust gas hose, approx. 4 meters
- Pressurized water tank, 10liters
- Dimensions(LxWxH): 480x300x490 mm
- weight: 20 kg without drillbit
- Drill bit connection 3-bolt flange or 1¼" UNC connection



Model	Motor	Power	Speed range	Order No
FB200	STIHL-2-stroke-motor GÖLZ-3-hole-flange (with pressurized water tank)	2,8kW (3,8 HP)	600 rpm	0295 201 2010

GÖLZ KB200 • Core drilling machine

- Coresampling in asphalt and concrete pavements
- Coring to place hand railings
- Coring to place barrier posts
- Coring of ceiling openings
- Core bilster lights at airfields
- Core installation of motorway crash barriers
- weight: 53 kg

Inclusive tool kit, pressurised water tank and exhaust gas hose!



Technical data - Extent of delivery
Twin column drill rig with standing plates and roller guides, stroke 630mm
STIHL- 2-stroke engine, 2,8 KW (3,8 HP)
Speed gear box 600 rpm, incl. flushing head
Water supply tank, pressure type, 10 litres incl. hose
Exhaust gas hose 4 meters keeps fumes away from working place

Drill range	Motor	Power	Speed range	Order No
Ø 107 - 200 mm	STIHL 2-stroke-petrol-motor	2,8 KW (3,8 HP)	600 rpm	0295 202 2000
Ø 50 - 280 mm	GBM30 electric motor	3,0KW, 230V, 50HZ, PRCD	220/500/935 rpm	0295 202 1010
Ø 107 - 200 mm	LZL15 air motor	2,4KW (3,7 HP) 3m³ air usage	600 rpm	0295 202 1020

Accessories for KB200	Order No
Core tongs for core sample Ø 50mm	0296 000 0082
Core tongs for core sample Ø 100mm	0296 000 0088
Core tongs for core sample Ø 150mm	0296 000 0092
Core tongs for core sample Ø 200mm	0296 000 0096